

WIDTH

TYPE OF BELT	PITCH [mm]	WIDTH [mm]	WIDTH TOLERANCE [mm]
T5	5	6÷150	+ 0.5
T10	10	10÷150	+ 0.5
T20	20	25÷150	+ 1.0
AT5	5	6÷150	+ 0.5
AT10	10	10÷150	+ 0.5
ATG10	10	25÷150	+ 0.5
AT20	20	25÷150	+ 1.0
MTD8	8	10÷150	+ 0.5
RPP5	5	6÷150	+ 0.5
RPP8	8	10÷150	+ 0.5
RPP14	14	25÷150	+ 1.0
P2	-	10÷100	+ 0.5
XL	5.08	6.35÷152.4	+ 0.5
L	9.525	9.53÷152.4	+ 0.5
H	12.7	12.7÷152.4	+ 0.5
XH	22.225	12.7÷152.4	+ 1.0

Special width tolerance on request.

THICKNESS

TYPE OF BELT	NOMINAL THICKNESS [mm]	THICKNESS TOLERANCE [mm]
T5	2.2	+ 0.15
T10	4.5	+ 0.3
T20	8	+ 0.45
AT5	2.7	+ 0.2
AT10	4.5	+ 0.3
ATG10	4.5	+ 0.3
AT20	8	+ 0.45
MTD8	5.6	+ 0.3
RPP5	3.8	+ 0.2
RPP8	5.4	+ 0.3
RPP14	10	+ 0.4
P2	2	+ 0.3
XL	2.3	+ 0.3
L	3.6	+ 0.3
H	4.3	+ 0.3
XH	11.2	+ 0.5

All MEGAFLEX belts are grinded in the back. Special thickness and special tolerance are available on request.

WEIGHT

BELT WEIGHT (gr./mt)										
TYPE WIDTH (mm)	10	16	25	32	50	75	100	150		
T5	25	40	65	80	110	160	210	320		
T10	53	72	133	144	256	398	530	750		
T20			200	250	400	600	800	1100		
AT5	30	48	75	96	160	245	328	490		
AT10		97	150	190	300	450	600	900		
AT20			270	350	500	750	1000	1420		
RPP5	39	59	98	125	195	290	390	590		
RPP8	66	105	164	197	328	490	656	990		
RPP14			295	380	590	880	1175	1770		
MTD8	65	104	162	210	325	487	650	975		
P2										
WIDTH (inch)	025	037	050	075	100	150	200	300	400	600
XL	16	23	31	46	61	91	122	183	244	366
L		33	45	68	90	135	180	270	360	540
H		38	55	83	110	160	220	325	430	650
XH					265	400	530	800	1060	1600

The table refers to standard belts and standard cords.